



# **RUST & CORROSION INHIBITOR** UNSURPASSED PROTECTION AGAINST RUST & OXIDATION

Rust Pro<sup>™</sup> Rust Inhibitor is an oil-dispersed, thixotropic formula capable of providing up to 5 years protection in indoor storage and 2-3 years protection outdoors.

For carbon steel or any exposed metal or painted surface in high-salt environments. Proven and used by major oil & gas companies for their stack-out programs and pipe protection.

#### UNTREATED VS TREATED



#### **KEY PERFORMANCE BENEFITS:**

 Long-term protection for ferrous and nonferrous parts for up to 5 years indoors and 2-3 years outdoors.

- •Once on the surface of the part, Rust Pro becomes a semi solid reducing drips and runoff.
- Superior clean-ability it can be easily removed with an alkaline cleaner.



3/16" inch thick bare steel. Right side brushed with **Rust Pro** and wiped off. Steel exposed to open air (67°F, 63% humidity) and muriatic acid for 24 hours.

### **USE RUST PRO:**

•On parts exposed to salt spray environments.

- •When parts will be subjected to long term storage or transportation.
- •When maximum protection is required against corrosion.

### **APPLICATIONS:**

CAN BE SPRAYED OR BRUSHED FOR EVEN COATING ON THE SURFACE

Apply undiluted for maximum protection. The product can be applied by airless spray or dip. Target application film thickness is 2ml. When dipping, the tank should be agitated so that the product becomes fluid and completely coats all surfaces.

- Airless sprayer 11 m<sup>2</sup> per litre (450 sq. ft. per gallon)
- Paint roller 15 m<sup>2</sup> per litre (600 sq. ft. per gallon)
- Brush 16 m<sup>2</sup> per litre (650 sq. ft. per gallon)



## **OHARACTERISTICS:**

Appearance of Fluid	Hazy Blue Translucent Semi Solid	
Odor	Trace of Petroleum	
Viscosity cSt @ 40°C	Semi Solid	
Pour Point	150°F	
	150 F	
Specific Gravity	.880992	

ProOne#	Size	Case Pack
41001	1 gallon/3.78L	4
41005	5 gallon/18.9L	1
41055	55 gallon/208L	1

@ProOneAus1



www.pro-one.net.au

Sales: 1800 427 5625 / (02) 9793 2511