

Page 1 of 6 PRO1-019

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation)

1. PRODUCT & COMPANY IDENTIFICATION

	11 1 100001 & COMM / ATT IDENTIFICATION							
1.1	Product Name:	ProOne® WIREGLIDE WIRELINE LUBRICANT						
1.2	Chemical Name:	Mineral Oil						
1.3	Synonyms:	NA NA						
1.4	Trade Names:	ProOne® Wireglide Wireline Lubricant						
1.5	Product Uses & Restrictions:	Lubricant and Cleaning Grease						
1.6	Distributor's Name:	Pro-1-One Lubrication Australia PTY LTD						
1.7	Distributor's Address:	6/165 Rookwood Rd, Yagoona NSW 2199, Sydney Australia						
1.8	Emergency Phone:	Poisons Information Centre: Australia: 13 11 26 New Zealand: 0800 764 766						
1.9	Business Phone / Fax:	Tel: +61 1300 00 7761						

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

4.1

First Aid:

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE DAMAGE. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

Classification: Asp. Tox. 1; Skin. Irrit. 2; Eye Dam. 1; Aq. Chronic 2

<u>Hazard Statements</u> (H): H304 – May be fatal if swallowed and enters airways. H315 – Causes skin irritation. H318 – Causes serious eye damage. H411 – Toxic to aquatic life with long lasting effects.

Precautionary Statements (P): P264 – Wash thoroughly with soap and water after handling. P280 – Wear protective gloves/eye protection. P273 – Avoid release to the environment. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P321 – Specific treatment see this container label. P332+P313 – If skin irritation occurs: Get medical advice/attention. P362+P364 – Take off contaminated clothing and was it before reuse. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 – Immediately call a POISON CENTER/doctor. P391 – Collect spillage. P405 – Store locked up. P501 – Dispose of contents/container to an approved waste disposal plant.



3 COMPOSITION & INGREDIENT INFORMATION

3. COMPOSITION & MOREDIEM IN ORMATION													
					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	om		ppm			ppm	,,,	
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
DISTILLATES (PETROLEUM),	64742-58-1	NA	265-156-6	NA	(5)	(10)	(5)	NA	NA	(5)	NA	NA	OIL MIST
HYDROTREATED SPENT	Asp. Tox 1; H3	04		55							*	-	
LITHIUM HYDROXIDE	1310-66-3	NA	215-183-4	NA	1	NA	1	NF	NF	1	NA	NA	i.
MONOHYDRATE	Acute Tox. 4; Skin Corr. 1A; H302, H314												
DISTILLATES (PETROLEUM),	64742-54-7	PY8035501	265-157-1	NA	5	NF	NF	NF	NF	5	NF	NF	MIST
HYDROTREATED HEAVY*	Asp. Tox. 1; H304												
SEVERELY HYDROTREATED	64742-52-5	NA	265-155-0	NA	(5)	(10)	(5)	NA	NA	(5)	NA	NA	OIL MIST
NAPHTHENIC PETROLEUM OIL *	Asp. Tox. 1; H304												
SOLVENT REFINED HEAVY	64741-96-4	PY8040000	265-097-6	NA	5	NA	NF	NF	NF	NA	NA	NA	MIST
NAPHTHENIC DISTILLATE					100 Ale								10 10
HYDROXYSTEARIC ACID	106-14-9	NA	203-366-1	NA	NA	NA	NF	NF	NF	NA	NA	NA	
THE REAL PROPERTY OF THE PROPE	Ĩ.												

* contains ≤ 3.0% DMSO (DIMETHYLSULFOXIDE) per IP 346. ** contains ≤ 0.1% BENZENE.

Ingestion:

4. FIRST AID MEASURES

DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control

		Center or local emergency telephone number for assistance and instructions. Seek immediate medical	
		attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.	
	Eyes:	If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes,	
		holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.	
	Skin:	Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned.	
	Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek	

immediate medical attention. If breathing stops, perform artificial respiration.



SDS Revision: 1.0

PRO1-019

Page 2 of 6

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision Date: 2/22/2021 Classification of the Hazardous Chemical (in accordance with WHS Regulation) 4. FIRST AID MEASURES – cont'd Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: May cause transient mild-eye irritation with short-term contact with liquid, spray or mist. Eyes: This product can cause mild, transient skin irritation with short-term exposure. This product can cause Skin: allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Inhalation: No significant adverse health effects are expected to occur upon short-term exposure to this product. Aspiration of liquid into the lungs can cause severe lung damage or death. 4.3 Symptoms of Overexposure Overexposure in eyes may cause redness, itching and watering. Eyes: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product Skin: can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 4.4 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects. 4.6 Target Organs: Eyes, Skin, Respiratory System 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). FLAMMABILITY 1 0 PHYSICAL HAZARDS PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus, zinc and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. 52 Extinguishing Methods: Dry chemical, foam, carbon dioxide, and water fog. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies 6. ACCIDENTAL RELEASE MEASURES 61 Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months. 73 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning. Keep container tightly closed when not in use. Do not store at temperatures above 120 °F (49 °C). Store away from strong oxidizers.



Page 3 of 6 PRO1-019

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation) 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC OSHA OTHER ppm (mg/m³) TLV STEL **ES-TWA** ES-STEL **ES-PEAK** PEL STEL IDLH **CHEMICAL NAME(S)** DISTILLATES (PETROLEUM). HYDROTREATED (5) (10)(5) NA NA (5) NA NA MIST HYDROTREATED SPENT LITHIUM HYDROXIDE 1 NA 1 NF NF 1 NA NA MONOHYDRATE DISTILLATES (PETROLEUM), NF 5 5 NF NF NF NF MIST **HYDROTREATED HEAVY*** SEVERELY HYDROTREATED OIL MIST (5) (10)(5) (5) NA NA NA NA NAPHTHENIC PETROLEUM OIL SOLVENT REFINED HEAVY NF NF NF NF NF MIST NAPHTHENIC DISTILLATE Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. 8.4 Eye Protection: Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available. 8.5 Hand Protection: Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g. neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. Remove contaminated clothing. Launder contaminated clothing before reusing. Contaminated leather goods should be removed promptly and discarded. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Green colored grease 9.2 Odor No odor 9.3 Odor Threshold: NA 9.4 pH: NA 9.5 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 96 NA Range: 9.7 Flashpoint: 219 °C (426 °F) Upper/Lower Flammability 9.8 Limits: 9.9 Vapor Pressure: NA 9.10 Vapor Density: NA 9.11 Relative Density: 0.786 @ 15.6 °C 9.12 Solubility: Insoluble in water Partition Coefficient (log Pow): 9.13 NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA 9.16 Viscosity: NA 9.17 Other Information Evaporation Rate: <1 (n-BuAc=1) 10. STABILITY & REACTIVITY Stability: 10.1 Stable at normal temperatures Hazardous Decomposition 10.2 Fumes, smoke, oxides of carbon and nitrogen. 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Open flames, sparks, high heat, and close proximity to incompatible substances Incompatible Substances: 10.5 Strong oxidizing agents.



Page 4 of 6 PRO1-019

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021 Classification of the Hazardous Chemical (in accordance with WHS Regulation) 11. TOXICOLOGICAL INFORMATION Inhalation: NO Ingestion: YES Absorption: YES Routes of Entry: 11.1 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is not presented in this document. 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested. 11.4 Chronic Toxicity Suspected Carcinogen: 11.5 No. 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. 11.7 Irritancy of Product: See section 4.3 11.8 Biological Exposure Indices: ΝE Physician Recommendations: 11.9 Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There are no specific data available for this product. Effects on Plants & Animals: 12.2 There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local hazardous waste laws. 13.2 Special Considerations: If the material is unsuitable for recycling or reclamation, enclosed-controlled incineration is recommended unless otherwise prohibited by local ordinance. 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 14.1 49 CFR (GND): **NOT REGULATED** 14.2 IATA (AIR): **NOT REGULATED** IMDG (OCN): 143 **NOT REGULATED** TDGR (Canadian GND): 14.4 **NOT REGULATED** ADR/RID (EU): 14.5 NOT REGULATED SCT (MEXICO): 14.6 NOT REGULATED 14.7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements: 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: TSCA Inventory Status: 15.3 The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 NA 15.5 Other Federal Requirements: None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) Lithium Hydroxide Monohydrate is found on the following state criteria lists: NJ and PA. 15.7 State Regulatory Information: No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). Other Requirements: 15.8 The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Distillates (Petroleum), Paraffinic: Harmful (Xn). Risk Phrases (R): 65 - Harmful: may cause lung damage if swallowed. Safety Phrases (S): 53-45 - Avoid exposure - obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible)



Page 5 of 6 PRO1-019

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation) 16. OTHER INFORMATION DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES Other Information: SERIOUS EYE DAMAGE. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Wash thoroughly with soap and water after handling. Wear protective gloves/eye protection. Avoid release to the environment. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Specific treatments see this container label. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and was it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Collect spillage. Store locked up. Dispose of contents/container to an approved waste disposal plant. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & ProOne, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Pro-1-One Lubrication Australia PTY LTD 16.4 Prepared for: 6/165 Rookwood Rd, Yagoona NSW 2199, Sydney Australia Tel: +61 1300 007 761 e-mail: info@pro-one.net.au http://www.pro-one.net.au
ShipMate, Inc. 16.5 Prepared by: P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com



Page 6 of 6 PRO1-019

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

SDS Revision: 1.0

SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation)

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number					
EXPOSURE LIMITS IN AIR:					
ACGIH	American Conference on Governmental Industrial Hygienists				
C Ceiling Limit					
ES Exposure Standard (Australia)					
IDLH Immediately Dangerous to Life and Health					
OSHA	U.S. Occupational Safety and Health Administration				
PEL Permissible Exposure Limit					
STEL Short-Term Exposure Limit					
TLV Threshold Limit Value					
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard				
1 Slight Hazard					
2	2 Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE PARTY OF THE P	
D		THE PARTY OF THE P	
E			
F		1	(2)





















Full Face Respirator

Dust & Vapor Half-

Full Face Respirator

Airline Hood/Mask or SCBA


OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit					
mg/m3	milligrams per cubic meter					
NA	NA Not Available					
ND	ND Not Determined					
NE	NE Not Established					
NF	NF Not Found					
NR	No Results					
ppm	parts per million					
SCBA	Self-Contained Breathing Apparatus					

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA							
FLAMMABILIT	FLAMMABILITY LIMITS IN AIR:						
Autoignition Minimum temperature required to initiate combustion in air with n Temperature source of ignition							
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive
TOYICOL O	CICAL INFORMATION:



LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s					
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal					
ppm	Concentration expressed in parts of material per million parts					
TDio	Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom					
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects					
TC, TC _o , LC _{io} , & LC _o						
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
RTECS	Registry of Toxic Effects of Chemical Substances					
BCF	Bioconcentration Factor					
TLm	Median threshold limit					
log Kow or log Koc	Coefficient of Oil/Water Distribution					

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System							
DOT	U.S. Department of Transportation							
TC	Transport Canada							
EPA	U.S. Environmental Protection Agency							
DSL Canadian Domestic Substance List								
NOHSC National Occupational Health and Safety Commission (Australia)								
NDSL	Canadian Non-Domestic Substance List							
PSL	Canadian Priority Substances List							
TSCA	U.S. Toxic Substance Control Act							
EU	European Union (European Union Directive 67/548/EEC)							
WGK	Wassergefährdungsklassen (German Water Hazard Class)							
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System							

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(4)	(4)		(T)	(4)		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

F.T.	《》	N. S.	*	8	Q	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

\Diamond		③	\Diamond			\Diamond		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment