

Page 1 of 7 PRO1-021

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation)

1. PRODUCT & COMPANY IDENTIFICATION

	I. PRODUCT & COMPANY IDENTIFICATION							
1.1	Product Name:	ProOne® FUEL MAXIMIZER						
1.2	Chemical Name:	Solvent Blend						
1.3	Synonyms:	NA NA						
1.4	Trade Names:	ProOne® Fuel Maximizer						
1.5	Product Uses & Restrictions:	Fuel Additive						
1.6	Distributor's Name:	Pro-1-One Lubrication Australia PTY LTD						
1.7	Distributor's Address:	6/165 Rookwood Rd, Yagoona NSW, 2199 Sydney Australia						
1.8	Emergency Phone:	Poisons Information Centre: Australia: 13 11 26 New Zealand: 0800 764 766						
1.9	Business Phone / Fax:	Tel: +61 1300 00 7761						
	1,000							

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).

DANGER! HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN, OR IF INHALED. SUSPECTED OF CAUSING CANCER. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. VERY TOXIC TO AQUATIC LIFE.

Classification: Acute Tox. 4, Carc. 2, Skin Irrit. 2, Eye Irrit. 2, Aq. Chronic 1

<u>Hazard Statements</u> (H): H302 – Harmful if swallowed. H312 – Harmful in contact with skin. H332 – Harmful if inhaled. H351 – Suspected of causing cancer. H315 – Causes skin irritation. H319 – Causes serious eye irritation. H400 – Very toxic to aquatic life.

Precautionary Statements (P): P201 - Obtain special instructions before use. P202 - Do not in handle until all safety precautions have been read and understood. P261 - Avoid breathing fume/ vapors. P264 - Wash thoroughly with soap and water after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 -Wear protective gloves/protective clothing/eye protection/face protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 - Rinse mouth. P308+P313 - If exposed or concerned: Get medical advice/attention. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P321 - Specific treatment - see Section 4 of this Safety Data Sheet. P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: get medical advice/attention. P273 - Avoid release to the P391 - Collect spillage. P405 - Store locked up. P501 - Dispose of environment. contents/container to licenses treatment, storage and disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

	EXPOSURE LIMITS IN AIR (mg/m³)						ng/m³)						
					AC	GIH		NOHSC			OSHA		
					PI	om		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
SOLVENT NAPHTHA*	64742-94-5	WF3100000	926-273-4	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
SOLVENT NAPHTHA	Asp. Tox. 1; F	Asp. Tox. 1; H304											
NADUTUAL ENE	91-20-3	QJ0525000	202-049-5	3-7	10	15	10	52	NF	10	15	250	
NAPHTHALENE	Acute Tox. 4;	Acute Tox. 4; Carc. 2; Aq. Acute 1; Aq. Chronic 1; H302, H351, H400, H410											
ORGANOMETALLIC	NA	NA	NA	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
COMPOUNDS				100	702 703						71		THE STATE OF THE S
1.2.4-TRIMETHYLBENZENE	95-63-6	DC3325000	202-436-9	0.1-1	25	NA	25	NF	NF	NA	NA	NA	25 NIOSH
1,2,4-1 RIME I ITT LIBENZENE	Flam. Liq. 3;	Flam. Liq. 3; Acute Tox. 4 *; Eye Irrit. 2; STOT SE 3; Skin Irrit. 2; Aq. Chronic 2; H226, H332, H319, H335, H315, H411											
ProOne® PROPRIETARY	NA	NA	NA	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	
Proune PROPRIETARY		50		40.0	000	** **							7.7
contains < 0.1% Benzene	•												



Page 2 of 7 SAFETY DATA SHEET PRO1-021 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021 Classification of the Hazardous Chemical (in accordance with WHS Regulation) 4. FIRST AID MEASURES First Aid: DO NOT INDUCE VOMITING. Contact ChemTrec +1 (800) 424-9300 or the nearest Poison Control Center Ingestion: or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Eyes: If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or Skin: the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned. Inhalation: Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention. 4.2 Effects of Exposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Eyes: Exposure to mists/fumes/vapors/spray may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering. Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Drowsiness, dizziness, headaches and nausea. 4.3 Symptoms of If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Overexposure: Exposure to mists/fumes/vapors/spray may cause eye irritation. Symptoms of overexposure may include Eyes: redness, itching, irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose Inhalation: and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.4 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of fumes/vapors can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. 4.5 Chronic Health Effects: Possible allergic dermatitis in some sensitive individuals. 4.6 Target Organs: Eyes, Skin, Respiratory System, Central Nervous System (CNS) Medical Conditions 4.7 Pre-existing dermatitis, other skin conditions, and disorders of the target **HEALTH** 2 Aggravated by Exposure: organs (eyes, skin, CNS) may be more susceptible to the effects of this 2 **FLAMMABILITY** substance. PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. 5.2 Extinguishing Methods: Dry chemical, foam, carbon dioxide, and water fog. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material

(e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open



9.12

9.13

9.14

9.15

9.16

9.17

Solubility

Decomposition

Other Information:

Temperature:

Viscosity:

Pow):

Partition Coefficient (log

Autoignition Temperature:

Insoluble

Evaporation Rate: < 1 (n-BuAc=1); VOC < 100%

NA

NA

NA

NA

SAFETY DATA SHEET

Page 3 of 7

PRO1-021 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021 Classification of the Hazardous Chemical (in accordance with WHS Regulation) 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Avoid breathing fume or spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in wellventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid contact with skin and clothing. Do not smoke while using. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. 7.2 Storage & Handling: Store in a cool, dry place. Do not place in hot water or near radiators, stoves or sources of heat. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Special Precautions: 7.3 Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH OTHER 8.1 ppm (mg/m³) STEL IDLH_ CHEMICAL NAME(S) TLV **ES-TWA ES-STEL ES-PEAK** PEL STEL NAPHTHAI FNF **NAPHTHALENE** 10 15 10 52 NF 10 15 250 1,2,4-TRIMETHYLBENZENE 25 NA 25 NF NF NA NA NA 25 NIOSH 8.2 Ventilation & Engineering Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not Controls anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134). 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. Safety glasses with side shields must be used when handling or using this product. A protective face 8.4 Eve Protection: shield is also recommended. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available. Hand Protection: 8.5 Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. Remove contaminated clothing. Launder contaminated clothing before reusing. Contaminated leather goods should be removed promptly and discarded. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Amber colored liquid Aromatic odor 9.2 Odor: 9.3 Odor Threshold: NA 9.4 pH: NA 9.5 Melting Point/Freezing NA 9.6 Initial Boiling Point/Boiling 158 °C (316 °F) Range: 9.7 Flashpoint >37.7 °C (>100 °F) 9.8 Upper/Lower Flammability NA 99 Vapor Pressure: <0.1 9 10 Vapor Density: Heavier than air 9 11 Relative Density: 0.89



Page 4 of 7 PRO1-021

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021 Classification of the Hazardous Chemical (in accordance with WHS Regulation) 10. STABILITY & REACTIVITY 10 1 Stability: Stable, when used as intended; unstable with heat or contamination 10.2 Hazardous Decomposition Thermal decomposition include oxides of carbon. Products: 10.3 Hazardous Polymerization: 10.4 Conditions to Avoid: Open flames, sparks, high heat, incompatible substances and direct sunlight. Incompatible Substances: 10.5 Avoid extreme heat and ignition sources. Store away from oxidizers. 11. TOXICOLOGICAL INFORMATION Routes of Entry: Ingestion: YES 11.1 This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is Toxicity Data: 11.2 available for some of the components of the product, but is not presented in this document. 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 11.4 Chronic Toxicity: This material may aggravate any pre-existing skin condition (e.g., dermatitis). Suspected Carcinogen: 11.5 Naphthalene is listed as IARC Group 2B (Possibly carcinogenic to humans); NTP13 Group 2 (Reasonably anticipated to be a human carcinogen); CA65 (cancer). 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. **Biological Exposure** 11.8 NE Indices: 11.9 Physician Treat symptomatically. Recommendations: 12. ECOLOGICAL INFORMATION 12 1 Environmental Stability: Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. 12.2 Effects on Plants & An environmental fate analysis has not been conducted on this specific product. However, plants and animals may experience harmful or fatal effects. 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13 1 Dispose of in accordance with federal, state, provincial and local hazardous waste laws. 13.2 Special Considerations: If the material is unsuitable for recycling or reclamation, enclosed-controlled incineration is recommended unless otherwise prohibited by local ordinance. 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): 14.1 UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA PETROLEUM), 3, III (LTD QTY, IP VOL ≤ 5.0 L); or CONSUMER COMMODITY, ORM-D – until 01/01/2021 IATA (AIR)*: 14.2 ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L); or UN1993, FLAMMABLE LIQUIDS, affh. N.O.S. (NAPHTHA PETROLEUM), 3, III (LTD QTY, IP VOL ≤ 1.0 L) IMDG (OCN): 14.3 UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA PETROLEUM), 3, III (LTD QTY, IP VOL $\leq 5.0 L$) 14 4 TDGR (Canadian GND): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA PETROLEUM), 3, III (LTD QTY, IP VOL ≤ 5.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL $\leq 5.0 L$) 14.5 ADR/RID (EU): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA PETROLEUM), 3, III (LTD QTY, IP VOL $\leq 5.0 L$) 14.6 SCT (MEXICO): UN1993, LIQUIDOS, INFLAMABLES, N.E.P. (NAFTA PETROLEO), 3, III (CANT. LTDA., IP VOL $\leq 5.0 L$) 14.7 ADGR (AUS): UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA PETROLEUM), 3, III (LTD QTY, IP VOL $\leq 5.0 L$)



Page 5 of 7 PRO1-021

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation) 15. REGULATORY INFORMATION SARA Reporting This product contains 1,2,4-Trimethylbenzene, and Naphthalene, substances subject to SARA Title III, Section 313 reporting requirements. 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 CFRCI A Reportable Naphthalene: 45.4 kg (100 lbs) Quantity (RQ): 15.5 Other Federal Naphthalene is listed as Hazardous Air Pollutants (HAPs). Naphthalene is listed as a Priority Pollutant under the CWA. Requirements: Naphthalene is listed as a Toxic Pollutant under the CWA. 15.6 Other Canadian This product has been classified according to the hazard criteria of the CPR and the SDS contains all Regulations: of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Naphtha (Petroleum) is found on the following state criteria lists: Massachusetts Hazardous Substances List (MA), New Information: Jersey Right-to-Know List (NJ), and Pennsylvania Right-to-Know List (PA). 1,2,4-Trimethylbenzene is found on the following state criteria lists: MA, NJ, and PA. Naphthalene can be found on the following state criteria list: FL, MA, MN, NJ, PA, WA and WI. None of the ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). WARNING! This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm. 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Solvent Naphtha: Harmful (Xn). Risk Phrases (R): 65 - Harmful: May cause lung damage if swallowed. Safety Phrases (S): 2-23-24-62 Note H - Keep out of reach of children. Do not breathe gas/ vapors/ spray. Avoid contact with skin. If swallowed do not induce vomiting: seek medical advice immediately and show this container or label where possible. Naphthalene: Harmful, Environmental Danger (Xn/N). Risk Phrases (R): 22-40-50-53 - Harmful if swallowed. Limited evidence of carcinogenic effect. Very toxic to aquatic organisms. May cause adverse long-term effects in the aquatic environment. Safety Phrases (S): 2-36/37-46-60-61 - Keep out of reach of children. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container label. This material and its container must be disposed of has hazardous waste. Avoid release to the environment. Refer to special instructions/ safety data



Page 6 of 7 PRO1-021

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation) 16. OTHER INFORMATION Other Information: DANGER! HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN, OR IF INHALED. SUSPECTED OF CAUSING CANCER. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. VERY TOXIC TO AQUATIC LIFE. Obtain special instructions before use. Do not in handle until all safety precautions have been read and understood. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke when using this product. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention. Avoid release to the environment. Collect spillage. Store locked up. KEEP OUT OF REACH OF CHILDREN. WARNING! This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm Terms & Definitions: See last page of this Safety Data Sheet. Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other 16.3 government regulations must be reviewed for applicability to this product. To the best of ShipMate's & ProOne, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition Prepared for: Pro-1-One Lubrication Australia PTY LTD 6/165 Rookwood Rd, Yagoona NSW 2199, Sydney Australia Tel: +61 1300 007 761 e-mail: info@pro-one.net.au http://www.pro-one.net.au Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 Training & Consulting

http://www.shipmate.com



Page 7 of 7 PRO1-021

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

SDS Revision: 1.0

SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation)

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number EXPOSURE LIMITS IN AIR: ACGIH American Conference on Governmental Industrial Hygienists C Ceiling Limit EXPOSURE Standard (Australia)			
ACGIH American Conference on Governmental Industrial Hygienists C Ceiling Limit ES Exposure Standard (Australia)			
C Ceiling Limit ES Exposure Standard (Australia)			
ES Exposure Standard (Australia)			
IDI II I I I I I I I I I I I I I I I I			
IDLH Immediately Dangerous to Life and Health			
OSHA U.S. Occupational Safety and Health Administration			
PEL Permissible Exposure Limit			
STEL Short-Term Exposure Limit			
TLV Threshold Limit Value			
TWA Time Weighted Average			

FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE PARTY OF THE P	
D		THE PARTY OF THE P	
E			
F		1	9





Face Shield & **Protective Eyewear**







Protective Clothing & Full Suit

Full Face Respirator





Airline Hood/Mask or SCBA


OTHER STANDARD ABBREVIATIONS:

ML	ML Maximum Limit				
mg/m3	mg/m3 milligrams per cubic meter				
NA Not Available					
ND Not Determined					
NE Not Established					
NF Not Found					
NR	No Results				
ppm	parts per million				
SCBA	Self-Contained Breathing Apparatus				

	NATIONAL FI	NATIONAL FIRE PROTECTION ASSOCIATION: NFPA								
ĺ	FLAMMABILI	TY LIMITS IN AIR:								
Autoignition Temperature Minimum temperature required to initiate combustion in air with source of ignition										
	LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source								
	UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source								

HAZARD RATINGS:

0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3 Severe Hazard					
4 Extreme Hazard					
ACD Acidic					
ALK	Alkaline				
COR	Corrosive				
₩	Use No Water				
ОХ	Oxidizer				
TREFOIL	Radioactive				
TOYICOLO	CICAL INFORMATION:				



LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TDio	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC Transport Canada						
EPA U.S. Environmental Protection Agency						
DSL Canadian Domestic Substance List						
NOHSC National Occupational Health and Safety Commission (Australia)						
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(4)	(4)	②	(T)	(49)		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

I.	《》	N. S.	*	8	Q	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond					\$
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment