

Page 1 of 6 PRO1-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 2/22/2021 Classification of the Hazardous Chemical (in accordance with WHS Regulation) **1. PRODUCT & COMPANY IDENTIFICATION** 1.1 Product Name: ProOne[®] INDUSTRIAL OIL CONCENTRATE 12 Chemical Name Mineral Oil Mixture 1.3 Synonyms NA 1.4 Trade Names: ProOne[®] Industrial Oil Concentrate 15 Product Uses & Restrictions Lubricating Oil 1.6 Distributor's Name Pro-1-One Lubricant Australia PTY LTD 1.7 Distributor's Address 6/165 Rookwood Rd, Yagoona NSW 2199, Sydney, Australia 1.8 Emergency Phone: Poisons Information Centre: Australia: 13 11 26 New Zealand: 0800 764 766 Business Phone / Fax: Tel: +61 1300 00 7761 1.9 2. HAZARDS IDENTIFICATION 2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES DAMAGE TO CENTRAL NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE. CAUSES SKIN IRRITATION. CAUSES EYE IRRITATION. Classification: Asp. Tox. 1, Skin Irrit. 2, Eye Irrit. 2B, STOT RE 1 Hazard Statements (H); H304 – May be fatal if swallowed and enters airways. H315 – Causes skin irritation. H320 - Causes eve irritation. H372 - Causes damage to central nervous system (CNS) through prolonged or repeated exposure. Precautionary Statements (P): P260 - Do not breathe fumes/mist/vapors/spray. P264 - Wash hands and exposed skin areas with soap and warm water thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P280 - Wear protective gloves/protective clothing/eye P301+P310 - IF SWALLOWED: Immediately call a POISON protection/ face protection. CENTER/doctor. P331 - Do NOT induce vomiting. P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P405 - Store locked up. P501 - Dispose of contents/container to licenses treatment, storage and disposal facility (TSDF) 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-RTECS No. EINECS No TLV STEL PEAK PEL STEL IDLH OTHER CHEMICAL NAME(S) CAS No. % TWA STEL DISTILLATES (PETROLEUM), 64742-54-7 PY8035501 NF NF NF NF 5 NF NF MIST 265-157-1 30-60 5 HYDROTREATED HEAVY Asp. Tox. 1; H304 PARAFFINIC* 64742-58-1 NA 265-156-6 NA (5) (10) (5) NA NA (5) NA NA OIL MIST DISTILLATES (PETROLEUM), HYDROTREATED SPENT Asp. Tox 1; H304 WJ8925000 232-489-3 15-40 100 NA NF 790 NF 500 NA 20000 (350) NIOSH 8052-41-3 **ODORLESS MINERAL SPIRITS**** Flam. Liq. 2, Asp. Tox. 1, STOT RE 1; H226, H304, H372 471-34-1 FF9335000 207-439-9 5-10 10 5 NF NF NF 10 5 NA RESP DUST CALCIUM CARBONATE INA NA NA NA NF NF NF NA NA ≤ 1.0 NA NA ProOne[®] PROPRIETARY * contains ≤ 3.0% DMSO (DIMETHYLSULFOXIDE) per IP 346. ** contains ≤ 0.1% BENZENE 4. FIRST AID MEASURES DO NOT INDUCE VOMITING. Contact ChemTrec +1 (800) 424-9300 or the nearest Poison Control Center 41 First Aid: Ingestion: or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, Eyes: holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or Skin: the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned. Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Inhalation: Seek immediate medical attention.



Page 2 of 6 PRO1-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

SDS Revision: 1.0

SDS Revision Date: 2/22/2021

water

Classification of the Hazardous Chemical (in accordance with WHS Regulation) FIRST AID MEASURES – cont'd 4.2 Effects of Exposure: Ingestion: If product is swallowed, may cause gastrointestinal disturbance. Exposure to mists/fumes/vapors/spray may cause eye irritation. Symptoms of overexposure may include Eyes: redness, itching, irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose Inhalation: and respiratory tract. Drowsiness, dizziness, headaches and nausea. 4.3 Symptoms of If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Overexposure: Eves: Exposure to mists/fumes/vapors/sprav may cause eve irritation. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in <u>Skin</u>: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea 44 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of fumes/vapors can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Chronic Health Effects: 4.5 Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects. 46 Target Organs: Eyes, Skin, Respiratory System, Central Nervous System (CNS) 47 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the target HEALTH 1 Aggravated by Exposure: organs (eyes, skin, CNS) may be more susceptible to the effects of this FLAMMABILITY 1 substance. PHYSICAL HAZARDS 0 **PROTECTIVE EQUIPMENT** В EYES SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This material can burn but will not readily ignite. This material will release vapors when heated above 51 the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. 5.2 Extinguishing Methods: Dry chemical, foam, carbon dioxide, and water fog. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of



Page 3 of 6 **PRO1-024**

SDS Revision Date: 2/22/2021

 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards
 SDS Revision: 1.0

 Classification of the Hazardous Chemical (in accordance with WHS Regulation)
 SDS Revision: 1.0

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months.
7.3	Special Precautions:	Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning. Keep container tightly closed when not in use. Do not store at temperatures above 120 °F (49 °C). Store away from strong oxidizers.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits:		AC	GIH		NOHSC			OSHA	<u> </u>	OTHER
	ppm (mg/m ³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	5	NF	NF	NF	NF	5	NF	NF	MIST
		DISTILLATES (PETROLEUM), HYDROTREATED SPENT	(5)	(10)	(5)	NA	NA	(5)	NA	NA	MIST
		ODORLESS MINERAL SPIRITS	100	NA	NF	790	NF	500	NA	20000	(350) NIOSH
		CALCIUM CARBONATE	10	5	NF	NF	NF	10	5	NA	RESP DUST
8.2	Ventilation & Engineering Controls:	When working with large quantities that an eyewash station, sink or was							exhaust	ventilatio	on, fans). Ensure
8.3	Respiratory Protection:	No special respiratory protection necessary, use only respiratory p §1910.134, or applicable U.S. state E.C. member states, or Australia. exposure levels are anticipated, a f pre-filter should be used. Protection	protection regula If ele NIOSH-	on auth tions, or vated a approve	orized per the appro- airborne co ed organic	er U.S. O opriate sta oncentratio vapor res	SHA's requindards of Cons above pirator equi	uireme Canada applica pped v	nt in 2 a, its pro able wo with a d	29 CFR ovinces, orkplace	
8.4	Eye Protection:	Safety glasses with side shields m shield is also recommended. Wear Have suitable eye wash water availa	goggle								6
8.5	Hand Protection:	Use gloves constructed of chemic frequent or prolonged contact is ex appropriate standards of Canada, o	pected	. If neo	essary, re	efer to U.S					
8.6	Body Protection:	Avoid prolonged and/or repeated neoprene or Tyvek [®]) if splashing o long-sleeves, apron, boots and ac contaminated clothing before reusi discarded. When handling large o should be available. Upon complet any exposed areas thoroughly with	r sprayi Iditional ng. Co Juantitie tion of v	ng conc facial ontamina s (e.g., work act	litions are protection ated leather ≥ 1 gallor tivities invo	present. F Remove er goods s n), eye wa	Protective c contamina should be reash stations	lothing ted clo emove and o	i should othing. d prom deluge	Launder ptly and showers	4

		9. PHYSICAL & CHEMICAL PROPERTIES
9.1	Appearance:	Straw/amber colored liquid
9.2	Odor:	Mild petroleum odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	226 °C (440 °F)
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	<0.1
9.10	Vapor Density:	NA
9.11	Relative Density:	0.96
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log Pow):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	NA



14.3

14.4

14.5

14.6

14.7

IMDG (OCN):

ADR/RID (EU):

SCT (MEXICO):

ADGR (AUS):

TDGR (Canadian GND):

NOT REGULATED

NOT REGULATED

NOT REGULATED

NOT REGULATED

NOT REGULATED

SAFETY DATA SHEET

Page 4 of 6 PRO1-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

SDS Revision: 1.0

SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation) **10. STABILITY & REACTIVITY** 10.1 Stability: Stable, when used as intended. 10.2 Hazardous Decomposition Carbon, nitrogen and sulfur oxides, hydrocarbons, phosgene. Products: 10.3 Hazardous Polymerization: Will not occur. Conditions to Avoid: 10.4 Heat, sparks, open flame and all possible ignition sources. 10.5 Incompatible Substances: Avoid contact with strong oxidizing agents, strong reducing agents, strong acids and strong alkalis.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: NO	Absorption:	YES	Ingestion:	YES
11.2	Toxicity Data:	This product has NOT been tested on anima available for some of the components of the p	product and is present	ed below:		
		Distillates, Petroleum, Solvent-Refined, Hea mg/kg. Odorless Mineral Spirits: LD ₅₀ (oral, ra		(oral, rat) > 5000	mg/kg; LD ₅₀ (derm	al, rabbit) > 2000
11.3	Acute Toxicity:	Mineral oil mists derived from highly refined of from single and short-term repeated exposur exposure levels include lung inflammatory re acute studies involving exposures to lower co produced no significant toxicological effects.	es to high concentrati eaction, lipoid granulo	ions of mineral oil n oma formation and	nists well above ap lipoid pneumonia.	plicable workplace In acute and sub-
11.4	Chronic Toxicity:	In long term studies (up to two years) no carc	inogenic effects have	been reported in ar	ny animal species te	ested.
11.5	Suspected Carcinogen:	This product contains a severely hydrotreate not considered a carcinogen.	d mineral oil with less	s than 3 % DMSO e	extract as measured	d by IP 346 and is
11.6	Reproductive Toxicity:	This product is not reported to produce reprod	ductive toxicity in hum	ans.		
	Mutagenicity:	This product is not reported to produce mutac				
	Embryotoxicity:	This product is not reported to produce embry				
	Teratogenicity:	This product is not reported to produce terato				
	Reproductive Toxicity:	This product is not reported to produce reprod	ductive effects in hum	ans.		
11.7	Irritancy of Product:	See section 4.3				
11.8	Biological Exposure Indices:	NE				
11.9	Physician Recommendations:	Treat symptomatically.				
		12. ECOLOGIC				
12.1	Environmental Stability:	There are no specific data available for this p				
12.2	Effects on Plants & Animals:	There are no specific data available for this p				
12.3	Effects on Aquatic Life:	There are no specific data available for this p				
		13. DISPOSAL (IONS		
13.1	Waste Disposal:	Dispose of in accordance with federal, state,			8	
13.2	Special Considerations:	If the material is unsuitable for recycling or re prohibited by local ordinance.				d unless otherwise
	1					
		14. TRANSPORTA	TION INFORM	IATION		
		umber, proper shipping name, hazard class & be required by 49 CFR, IATA/ICAO, IMDG and		up) is shown for eac	th mode of transpor	rtation. Additional
14.1	49 CFR (GND):	NOT REGULATED				
14.2	IATA (AIR):	NOT REGULATED				
	1					1 '



Page 5 of 6 PRO1-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

SDS Revision: 1.0

SDS Revision Date: 2/22/2021

Classification of the Hazardous Chemical (in accordance with WHS Regulation) 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: TSCA Inventory Status: 15.3 The components of this product are listed on the TSCA Inventory CERCLA Reportable 15.4 NA Quantity (RQ): 15.5 Other Federal This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority Requirements: pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA 15.6 Other Canadian This product has been classified according to the hazard criteria of the CPR and the SDS contains all Regulations: of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: Odorless Mineral Spirits is found on the following state criteria list(s): Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA) and Washington Permissible Exposures List (WA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Toxic (T). Risk Phrases (R): 45 - May cause cancer. Safety Phrases (S): 53-45 - Avoid exposure - obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). Odorless mineral spirits: Flammable (F). Risk Phrases (R): 12-65 - Highly flammable. Harmful: may cause lung damage if swallowed. Safety Phrases (S): 53-45 - Avoid exposure - obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). 16. OTHER INFORMATION Other Information: DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES DAMAGE TO CENTRAL NERVOUS 16.1 SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE. CAUSES SKIN IRRITATION. CAUSES EYE IRRITATION. Do not breathe fumes/mist/vapors/spray. Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Do not eat, drink or smoke when using this product. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store locked up. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other 16.3 Disclaimer: government regulations must be reviewed for applicability to this product. To the best of ShipMate's & ProOne, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: Pro-1-One Lubricant Australia PTY LTD 6/165 Rookwood Rd, Yagoona NSW 2199 Tel: +61 1300 00 7761 e-mail: info@pro-one.net.au http://www.pro-one.net.au 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Dangerous Goods Fax: +1 (310) 370-5700 Training & Consulting http://www.shipmate.com



Page 6 of 6 PRO1-024

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

Classification of the Hazardous Chemical (in accordance with WHS Regulation)

SDS Revision: 1.0

SDS Revision Date: 2/22/2021

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
EXPOSURE	LIMITS IN AIR:
ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average
FIRST AID M	EASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood CPR and provide oxygen to the body.

HMIS-	III HEALTH, FLAMMABILITY & I	REA	CTIVITY RATINGS:
0	Minimal Hazard		HEALTH
1	Slight Hazard		FLAMMABILITY
2	Moderate Hazard		PHYSICAL HAZARDS
3	Severe Hazard		PERSONAL PROTECTION
4	Extreme Hazard		

PERSONAL PROTECTION RATINGS:

Α	0		G	0		8			
в	0		Н				8		
С	0		I	0		8			
D	B		J			•	8		
Е	0		κ	6					
F	0		X		your sup handling		r SOPs fo s.		
Sa	afety Glasse	es Splash Goggles		e Shield 8 tive Eyew		Gloves			
	Boots	Synthetic Apron		Protective Clothing & Full Suit					
		8		9		3			
	Face Respir	rator Dust & Vapor Half- Mask Respirator DARD ABBREVIATIONS	Re	ull Face espirator	Ai	rline Hoo or SCI			
	-		5 :						
	ML ma/m2	Maximum Limit milligrams per cubic meter							
	mg/m3 NA	Not Available							
<u> </u>	ND	Not Determined							
	NE	Not Established							
	NF	Not Found							
	NR	No Results							
	ppm	parts per million							
	000								

SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FL/	AMMABILI	TY LIMITS IN AIR:
	Autoignition emperature	Minimum temperature required to initiate combustion in air with no other source of ignition
	LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
	UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

	RATING			and					AMP	ABILITY				
	_	nal Ha						r.	-CHIM		-		-	
	-	t Haza erate H		1						V	-	REA	CTIVITY	
	_	re Haz												
	_	me Ha												
AC			2010						<	1	X	2	>	
AL												\checkmark		
co	_													
1	V Use 1	No Wa	iter					HE	ALTI	H /	X			
0	X Oxidi	zer									~	· · · · ·	ECIAL	
TREFO	IL Radio	oactive	;											
TOXICOL	OGICA	l inf	ORM	ATI	ON:									
		LD ₅₀	Let	nal D	ose (s	olids	& liqui	ids) wh	ich k	ills 50%	of the	expos	ed animals	
		LC ₅₀	S Lott	nal o	oncent	ration	(0256	e) which	h kil	le 50% c	f the i	avnosa	d animal	
		ppm						-		aterial p				
								mptom		atoriai p			13	
		TCLo	-					ause a		otom				
TD _{1~}	, LD _{Io} , & L		-							se letha	or to:	kic effe	cts	
	TC, TC _o , LC _{lo} , & LC _o							,						
		IARC	Inte	rnati	onal A	<u>gen</u> cy	for R	esearc	h on	Cancer				
		NTP	Nat	iona	Toxico	ology	Progra	am						
	R	TECS	Reg	jistry	of Tox	cic Eff	ects o	f Chem	ical	Substan	ces			
		BCF	-		entratio									
		TL _m		Median threshold limit										
log l	K _{ow} or log	g K _{oc}	Coe	efficie	ent of C	Dil/Wa	ter Di	stributio	on					
REGULA														
WHMI	_		/orkplace Hazardous Material Information System											
DO		-	ment of Transportation											
	_			anada										
EP.			nmental Protection Agency											
DS			Iomestic Substance List											
NOHS	_		cupational Health and Safety Commission (Australia)											
NDS PS	_		on-Domestic Substance List riority Substances List											
TSC	_		Substance Control Act											
	_		nion (European Union Directive 67/548/EEC)											
WG				hrdungsklassen (German Water Hazard Class)										
HMIS-I		-		nt & Coatings Association Hazardous Materials Identification System										
WORKPL					-								-	
0	۲) (٥)	(り	C	Ð	(•	the second	æ	Ŕ	
Class A	Class B		Class (2	Class	D1	Clas	ss D2	Cla	ass D3	Cla	ss E	Class F	
Compressed	Flammab	le (Oxidizir	ng	Тох	ic	Irrit	ation	Infectious		Corr	osive	Reactive	
EC (67/54	48/EEC)	INFO	RMA	TIC	N:				I					
	/				_		-		_		_			
1		ANN I	N		¥	2	*	3	4.10			¢	×	
С	E		F		N			0		Т	Xi		Xn	
Corrosive	Explosiv	re F	lamma	ble	Harn	nful	Oxi	dizing	1	Гохіс	Irri	tant	Harmful	
CLP/GHS	6 (1272/2	2008/1	EC) F	PICT	OGR	AMS	:							
			5	<	3	H	УЧ,	S	go		><		Ł	
	Y				<u> </u>							~		
GHS01	GHS02	GH	5 03	GI	-IS04	GH	S05	GHS	06	GHS07	, ,	GHS08	GHS09	